



UPLUX
UL01X SERIES

OUTDOOR

UPLUX

UL01X SERIES



GENERAL SPECIFICATIONS :


Head Material	: Die-cast aluminium
Recessing Box	: Die-cast aluminium
Lamp Type	: Halogen/MH
Lamp holder	: GU53/G12
Voltage rating/ freq.	: 220-240V / 50-60 Hz
Control gear type	: HPF conventional control gear (MH) HF electronic transformer (HAL)
Power factor	: >0.9
Degree of protection	: IP 67
Optical configuration	: Pure anodized aluminium louver
Finishing	: Durable enamel finish
Glass	: 15mm Tempered safety glass
Static pressure	: 3000 Kg
Trim shape	: Standard Round (Square as option)

DESCRIPTIONS : UPLUX UL01X series is adjustable round/square shape uplight of stainless steel 304 trim that provides a professional lighting solution for landscape and facade lighting, using die casted aluminium housing and 15mm tempered safety glass can be used in all environments. It is also suitable for static pressure upto 3000kg.

APPLICATIONS : Landscape lighting designs, facade lighting and othe similar applications.

OPTIONS :

- Antiglare louver (add /AGL)
- Honey comp louver (add /HCL)
- Square stainless steel trim (add /SST)



SST



HCL



AGL





OUTDOOR

UPLUX

UL01X SERIES

SPECIFICATIONS :



Lamp type	: 12V Halogen	Metal Halide
Lamp wattage	: 50W/100W	20W MH
Beam angle	: 4°/8°/24°/45°	6°
Control gear	: HF electronic transformer	Electronic ballast



CODE	D	H
UPLUX [UL011]-50W HAL	220	262
UPLUX [UL012]-100W HAL	220	262
UPLUX [UL013]-20W MH	220	262

SPECIFICATIONS :



Lamp type	: Metal Halide
Lamp wattage	: 35W/70W
Beam angle	: 6°/12°/24°/32°
Control gear	: HPF conventional control gear



CODE	D	H
UPLUX [UL014]-35W MH	260	267
UPLUX [UL015]-70W MH	260	267

SPECIFICATIONS :




Lamp type	: Metal Halide
Lamp wattage	: 150W
Beam angle	: 6°/12°/24°/32°
Control gear	: HPF conventional control gear




CODE	D	H
UPLUX [UL016]-150W MH	330	350

WALL WASH VERSIONS


CODE	D	H
UPLUX [UL017]-70W MH WALL WASH	330	350
UPLUX [UL018]-150W MH WALL WASH	330	350




15° in both directions



UL016-UL018 mounting



UL014-UL015 mounting



UL011-UL013 mounting

Head office

Malaz - Salahidin Road
P.O Box 1246 Riyadh 11431

Tel : +966 11 477 77 00
Fax: +966 11 478 94 69

Western Region Office

Tahliya Street
P.O Box 20798 Jeddah 21465

Tel : +966 12 6650888
Fax: +966 12 6633413

Eastern Region Office

King Abdulaziz Street
P.O Box 8492 Dammam 31482

Tel : +966 13 8336509
Fax: +966 13 8329065

ContactUs@noortek.com



www.noortek.com