



# FLOODLUX

F05XA

# OUTDOOR

FLOODLUX

F05XA





## SPECIFICATIONS :

Housing	: Die-cast aluminum
Lamp Type	: Single ended MH / HPS
Lamp holder	: E40
Voltage rating/ freq.	: 220-240V / 50-60 Hz
Control gear type	: HPF conventional control gear
Power factor	: >0.9
Degree of protection	: IP 65
Optical configuration	: High purity anodized aluminium reflector
Finishing	: UV stabilized polyester powder coating, resistant to corrosive environment.
Seal	: Silicon gasket and silicone sealant
Glass	: Tempered safety glass

**DESCRIPTIONS :** FLOODLUX F05XA of Asymmetric general purpose flood light is the solution for high mast based open areas illumination design. Using of high quality die cast aluminium housing and protection glass make this product suitable for the most severe conditions with protection degree IP 65.

**APPLICATIONS :** Parking areas, play grounds, open areas and other similar applications.



CODE	W	D	H
FLOODLUX (F051A)-1000W MH	550	227	733
FLOODLUX (F052A)-1000W HPS	550	227	733



### **Head office**

Malaz - Salahidin Road  
P.O Box 1246 Riyadh 11431

Tel : +966 11 477 77 00  
Fax: +966 11 478 94 69

### **Western Region Office**

Tahliya Street  
P.O Box 20798 Jeddah 21465

Tel : +966 12 6650888  
Fax: +966 12 6633413

### **Eastern Region Office**

King Abdulaziz Street  
P.O Box 8492 Dammam 31482

Tel : +966 13 8336509  
Fax: +966 13 8329065

ContactUs@noortek.com



**[www.noortek.com](http://www.noortek.com)**