



**LED - D19A**  
**ADJUSTABLE**

# LED DOWNLIGHT



## DESCRIPTIONS


The D19A is a recessed adjustable LED downlight series with high quality die-cast aluminum body in powder-coated, Equipped with good quality aluminum reflector with 15D or 24D or 38D beam angles, available in different trims and reflectors option. Excellent heat sink capability to minimize the luminous degradation, remote LED driver.

## APPLICATIONS


General lighting, residential etc.

115

## PHOTOMETRIC DATA



## DIMENSIONS



## SPECIFICATIONS


Housing	Die casted aluminum
LED module type	COB LED chips
Voltage rating/ freq.	220-240V / 50-60 Hz
Driver	Constant current LED driver
Beam Angle	15°/24°/38°
Light output	90Lm/W
Degree of protection	IP40
Color temp.	3000K/4000K/6500K
Rated lifetime (L70)	50,000 Hrs (@25C°)

CODE	Wattage	Lumin	IP Rate	Color Temp.	Ø	H
D191A-20W	20W	1800LM	IP40	3K/4K/6.5K	128	140
D192A-25W	25W	2250LM	IP40	3K/4K/6.5K	128	140
D193A-30W	30W	2700LM	IP40	3K/4K/6.5K	128	140



### OPTIONS:

- Dimmable Driver 1 -10 / DALI
- Backup Emergency Kit 3H
- Frosted / Semi frosted glass diffuser


## MOUNTING SYSTEM



Product Overview



Connect power and fix the fixture into Ceiling



#### **Head office**

Malaz - Salahidin Road  
P.O Box 1246 Riyadh 11431

Tel : +966 11 4777 700  
Fax: +966 11 4789 469

#### **Western Region Office**

Tahliya Street  
P.O Box 20798 Jeddah 21465

Tel : +966 12 6650888  
Fax: +966 12 6633413

#### **Eastern Region Office**

King Abdulaziz Street  
P.O Box 8492 Dammam 31482

Tel : +966 13 8336509  
Fax: +966 13 8329065

[ContactUs@noortek.com](mailto:ContactUs@noortek.com)



**[www.noortek.com](http://www.noortek.com)**