

OUTDOOR

BOLUX



SPECIFICATIONS :



Head Material	: Die-cast aluminum
Housing	: Extruded aluminium tube
Lamp Type	: MH/HPS/CFL
Lamp holder	: E27/G24
Voltage rating/ freq.	: 220-240V / 50-60 Hz
Control gear type	: HPF conventional control gear (MH/HPS) HF electronic ballast (CFL)
Power factor	: >0.9
Degree of protection	: IP 65
Optical cofigutation	: Anodized aluminium louver
Finishing	: Durable enamel finish
Diffuser	: Impact resistant polycarbonate lens with UV inhabitant

DESCRIPTIONS : BOLUX series provide a professional lighting solution for residential and architectural lighting. Its die cast aluminium body, featuring high IK rating, protects all the fragile elements of the optics (light source, reflector, diffuser) from any external mechanical impacts.

APPLICATIONS : For commercial buildings, hospitals, yards, parks and walkways.

OPTIONS :

- Different MH Wattage 35W/70W
- Different HPS Wattage 50W/70W



CODE	D	H
GARDENLUX_OGL(N10-013)-HID-MH-35/70W-CON/PC [IP65] [E27] [BL](1070 MM)	200	1070
GARDENLUX_OGL(N10-013)-HID-HPS-50/70W-CON/PC [IP65] [E27] [BL](1070 MM)	200	1070

