



GARDENLUX

GNL02X SERIES





SPECIFICATIONS :

Housing	: Die-cast aluminium
Lamp Type	: MH / HPS
Lamp holder	: E27 / E40
Voltage rating/ freq.	: 220-240V / 50-60 Hz
Control gear type	: HPF conventional control gear
Degree of protection	: IP 55
Optical configuration	: Indirect mirror finish reflector
Glass	: Tempered protection glass
Suitable pole top	: 76 mm
Recemented pole height	: 3:6 mt
Diffuser	: Clear PC diffuser

DESCRIPTIONS : GL02X is a beautiful indirect light that provides new dimensional in landscape lighting designs. Using of die-cast aluminium and UV resistant PC lamp cover makes this series suitable for outdoor applications of IP55. Designed for use with metal halide 70W/150W MH E27 and 70W HPS/150W HPS lamps.

APPLICATIONS : Landscapes designs, parks and other similar applications



CODE	W	H
GARDENLUX [GNL 021]-70W MH	654	645
GARDENLUX [GNL 022]-150W MH	654	645
GARDENLUX [GNL 023]-70W HPS	654	645
GARDENLUX [GNL 024]-150W HPS	654	645



Head office

Malaz - Salahidin Road
P.O Box 1246 Riyadh 11431

Tel : +966 11 477 77 00
Fax: +966 11 478 94 69

Western Region Office

Tahliya Street
P.O Box 20798 Jeddah 21465

Tel : +966 12 6650888
Fax: +966 12 6633413

Eastern Region Office

King Abdulaziz Street
P.O Box 8492 Dammam 31482

Tel : +966 13 8336509
Fax: +966 13 8329065

ContactUs@noortek.com



www.noortek.com