



وحدة إنارة ليد خطية غاطسة
LED Proline SH_1
LINEAR LED RECESSED LIGHT

LINEAR LED RECESSED LIGHT

LED Proline SH_1



SPECIFICATIONS

LEDs Brand & Type	SMD2835
Number of LEDs	1
Color Temperature	3000K
CRI	>82
SDCM	<5
Beam Angel	38°
Luminous Flux	3208Lm
Life time L70 (hrs)	5 years
Optic Material	Stalinite
Overall Diameter (mm)	1000*33*80MM
Driver	built-in
Wattage	36W
Input Voltage	AC200-240V
Input Frequency	50/60HZ
Output Voltage	36V
Output Current	800mA
Power Factor	>0.5
IP Rating	IP20
Ambient Temperature	-25 °C < TA < 50 °C

Product Description:

Recessed Simple and lightweight lamp body structure, easy to installation and disassembly. Precise optical design, pure light color, perfect light spot to create excellent lightings. Integrated high grade LED Driver with stable performance and longer lifespan. Die-casting aluminum housing is durable, with white powder spraying on the surface.

Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Fullamps does not accept responsibility for any installation costs associated with the replacement of this product and Fullamps reserves the right to alter specifications without prior notice.

Watt	Power Factor	Dimension	Cut	Lumen	Output Current	Weight (kg)
36W	>0.5	1000*30*80MM	/	3208Lm	800mA	/

Head office

Mulaz - Salahidin Road
PO Box 1246 Riyadh 11431

Tel: +966 11 4777200
Fax: +966 11 4789469

Western Region Office

Tahliya Street
PO Box 20798 Jeddah 21469

Tel: +966 12 6650388
Fax: +966 12 6633413

Eastern Region Office

King Abdulaziz Street
PO Box 8492 Dammam 31482

Tel: +966 13 8336500
Fax: +966 13 8329055

ContactUs@noortek.com



www.noortek.com