



**WALLUX  
WL04X SERIES**

# WALLUX




## DESCRIPTIONS

WALLUX WL04X Series is a square bulkhead luminaire for outdoor applications. Using of high quality die cast aluminium housing and Opal PC diffuser make this product suitable for the most severe conditions with protection degree IP 65.


## APPLICATIONS

Electrical and mechanical rooms, building surroundings and other similar outdoor applications.

## PHOTOMETRIC DATA



## DIMENSIONS



## SPECIFICATIONS

Housing	High quality die-cast aluminum
LED module type	OSRAM / CREE LED
Voltage rating/ freq.	220-240V / 50-60 Hz
Driver	High quality high frequency integrated LED driver
Beam angles	90°
Degree of protection	IP 65
Operating Temp.	-10°C - 50°C
Diffuser	Santin transparent PC diffuser
Standard color temp.	3000K, 4000K, 6000K
Rated lifetime (L70)	50,000H

CODE	Wattage	Lumin	IP Rate	ColorTemp	L	W	H
WALLUX(WL041)-20W	20W	2500LM	IP65	4000K	340	181	236
WALLUX(WL041)-30W	30W	3750LM	IP65	4000K	340	181	236

## OPTIONS:

- Dimmable Driver 1 - 10 / DALI
- Backup Emergency Kit 1H/3H
- Color Temperature : 3000K, 4000K, 6500K

## MOUNTING SYSTEM

#### **Head office**

Malaz - Salahidin Road  
P.O Box 1246 Riyadh 11431

Tel : +966 11 4777 700  
Fax: +966 11 4789 469

#### **Western Region Office**

Tahliya Street  
P.O Box 20798 Jeddah 21465

Tel : +966 12 6650888  
Fax: +966 12 6633413

#### **Eastern Region Office**

King Abdulaziz Street  
P.O Box 8492 Dammam 31482

Tel : +966 13 8336509  
Fax: +966 13 8329065

[ContactUs@noortek.com](mailto:ContactUs@noortek.com)



**[www.noortek.com](http://www.noortek.com)**