



LED BOLLARD
BOLED 01X

LED BOLLARD



DESCRIPTIONS :

BOLED 01 series provide a professional lighting solution for residential and architectural lighting. Its die cast aluminium body, featuring high IK rating, protects all the fragile elements of the optics (light source, reflector, diffuser) from any external mechanical impacts.

APPLICATIONS :



For commercial buildings, hospitals, yards, parks and walkways.



SPECIFICATIONS

Housing	Extruded aluminum tube with die cast aluminum head
LED module type	LED
Voltage rating/ freq.	220-240V / 50-60 Hz
Driver	Electronic LED driver
Degree of protection	IP65
Optical configuration	High pure aluminum reflector
Finish	Black, White & Graphite
Diffuser	Transparent polycarbonate UV-stabilizer
Standard color temp.	3000K, 4000K, 6000K
Rated lifetime (L70)	50,000 hrs.

CODE	Wattage	Lumin	IP Rate	CCT	D	H
BOLED 011 - 8W	8W	800	IP65	3K/4K/6.5K	210	1000
BOLED 012 - 15W	15W	1500	IP65	3K/4K/6.5K	210	1000



OPTIONS :

- Standard electronic driver
- Dimming driver 1-10V
- DALI

Head office

Malaz - Salahidin Road
P.O Box 1246 Riyadh 11431

Tel : +966 11 4777 700
Fax: +966 11 4789 469

Western Region Office

Tahliya Street
P.O Box 20798 Jeddah 21465

Tel : +966 12 6650888
Fax: +966 12 6633413

Eastern Region Office

King Abdulaziz Street
P.O Box 8492 Dammam 31482

Tel : +966 13 8336509
Fax: +966 13 8329065

ContactUs@noortek.com



www.noortek.com